





APPLICATION CHECK SHEET

1 Application	<input type="radio"/> Temperature Control		<input type="radio"/> Constant Flow Control				
	<input type="radio"/> Other:						
2 Fluid Type	<input type="radio"/> Industrial Water	<input type="radio"/> City Water	<input type="radio"/> Ethylene Glycol	<input type="radio"/> Galden®			
	<input type="radio"/> Fluorinert™	<input type="radio"/> Silicone Oil	<input type="radio"/> Other:				
3 Pressure Condition	<input type="radio"/> Positive Pressure		<input type="radio"/> Negative Pressure				
4 Upper Flow Limit (Water at 0.4 MPa / 58 PSI ΔP) » Contact Proteus for limits with other liquids	<input type="radio"/> LPM →	<input type="radio"/> 10.4	<input type="radio"/> 24.5	<input type="radio"/> 48.8	<input type="radio"/> 75	<input type="radio"/> 133	
	<input type="radio"/> GPM →	<input type="radio"/> 2.8	<input type="radio"/> 6.5	<input type="radio"/> 12.8	<input type="radio"/> 20	<input type="radio"/> 35	
	<input type="radio"/> Other:						
5 Upstream Pressure	<input type="radio"/> MPa			<input type="radio"/> PSI			
6 Connection Size	<input type="radio"/> NPT →	<input type="radio"/> 1/4"	<input type="radio"/> 3/8"	<input type="radio"/> 1/2"	<input type="radio"/> 3/4"		
	<input type="radio"/> BSPT →	<input type="radio"/> 1/4"	<input type="radio"/> 3/8"	<input type="radio"/> 1/2"	<input type="radio"/> 3/4"		
	<input type="radio"/> SAE →	<input type="radio"/> 9/16-18		<input type="radio"/> 3/4-16			
7 Liquid Temperature Range	<input type="radio"/> 0-60°C / 32-140°F			<input type="radio"/> -40-130°C / -40-266°F			
	<input type="radio"/> 0-130°C / 32-266°F			<input type="radio"/> 0-180°C / 32-356°F			
	<input type="radio"/> -20-100°C / -4-212°F			<input type="radio"/> Other:			
8 Preferred O-Ring Material	<input type="radio"/> Buna-N (-30-100°C / -22-212°F)			<input type="radio"/> Viton® (-15-200°C / 5-392°F)			
	<input type="radio"/> EPDM (-45-130°C / -49-266°F)			<input type="radio"/> Silicone Rubber (-50-200°C / -58-392°F)			
9 Analog I/O	<input type="radio"/> 1-5 VDC	<input type="radio"/> 1-10 VDC	<input type="radio"/> 4-20 mA				
10 Mounting Direction	<input type="radio"/> 	<input type="radio"/> 	<input type="radio"/> 	<input type="radio"/> 			
11 Miscellaneous	<input type="radio"/> Assemble with Tofpine		<input type="radio"/> High Valve Operation Frequency				
	<input type="radio"/> Constant Air Bubbles in Fluid		<input type="radio"/> Additives in Fluid				
	<input type="radio"/> Constant Supply Pressure		<input type="radio"/> Pulsed Flow				
	Other Comments:						

NAME: _____ TITLE: _____
 COMPANY NAME: _____ DEPT.: _____
 ADDRESS: _____
 CITY: _____ STATE: _____ ZIP: _____
 E-MAIL: _____ PHONE: _____

Please send this completed form to Proteus Sales: » E-mail: sales@proteusind.com » Fax: (650) 965-0304